

Label And Description 1.58

Object Name	Field Name	Field Label	Field Description
Conversation_Recipient_Map__c	Conversation__c	Conversation	This field contains the value of the Conversation lookup.
SenderId_Profile_Map__c	Profile_Id__c	Profile Id	This field contains the profile ID related to the sender ID of the user.
SenderId_Profile_Map__c	SenderId_Lookup__c	SenderId Lookup	This field contains the ID to retrieve sender ID.
SenderId_Profile_Map__c	User__c	User	This field contains the user information related to the default sender ID.
Error_Log__c	Batch_Id__c	Batch Id	This field contains the batch ID if the error occurred in a batch.
Error_Log__c	Class_Name__c	Class Name	This field contains the class name where the error occurred.
Error_Log__c	Error_Message__c	Error Message	This field contains the description of the error.
Error_Log__c	Error_Status_Code__c	Error Status Code	This field contains the error code.
Error_Log__c	Error_Type__c	Error Type	This field contains the error type. The type can be: Generic, SOQL, Permission, or Custom.
Error_Log__c	Fields__c	Fields	Stores the fields of an object because of which the error originated.
Error_Log__c	Line_number__c	Line number	This field contains the line number of the class where error originated.
Error_Log__c	Object__c	Object	This field contains the object on which the error occurred.
Error_Log__c	User__c	User	This field contains the user for which the error occurred.

AccessibleChannels__c	IsMMSEnabled__c	Is MMS Enabled	This field contains the value whether MMS is enabled or not.
AccessibleChannels__c	IsSMSEnabled__c	Is SMS Enabled	This field contains the value whether SMS is enabled or not.
SMS_Batch_Execution_Tracker__c	Campaign__c	Campaign	This field contains the lookup of Campaign for which SMS batch was executed.
SMS_Batch_Execution_Tracker__c	Execution_Status__c	Execution Status	This field contains the execution status. The status can be: Queued, Processing, etc.
SMS_Batch_Execution_Tracker__c	Job_Id__c	Job Id	This field contains the job ID of the batch executed for sending SMS.
SMS_Magic_Package_Type__c	Expired__c	Expired	This field indicates the account subscription is Expired.
SMS_Magic_Package_Type__c	Package1__c	Package1	This field indicates the account subscription is Starter.
SMS_Magic_Package_Type__c	Package2__c	Package2	This field indicates the account subscription is Value.
SMS_Magic_Package_Type__c	Package3__c	Package3	This field indicates the account subscription is Automation.
SMS_Magic_Package_Type__c	Trial__c	Trial	This field indicates account is in the trial subscription period.
Converse_App__c	Action_Count__c	Number of Actions	This field contains the number of actions in a Converse App.
Converse_App__c	End_Date__c	End Date	This field contains the end date for Converse App.
Converse_App__c	ErrorMessages__c	Error Messages	This field contains the error message encountered in sending messages.

Converse_App__c	ErrorState__c	Error State	This field contains the value for the checkbox field if an error exists. The value can be TRUE or FALSE.
Converse_App__c	Object__c	Salesforce Object	This field contains the primary object for the Converse App.
Converse_App__c	Owner__c	Owner	This field contains the owner of the Converse App.
Converse_App__c	PrimaryType__c	PrimaryType	This field contains the primary purpose of Converse App. This purpose can be: Manual or Automation.
Converse_App__c	Purpose__c	Purpose	This field contains the purpose of the Converse App.
Converse_App__c	Start_Date__c	Start Date	This field contains the start date of the Converse App.
Converse_App__c	Status__c	Status	This field contains the current status of the Converse App. Status can be Draft, Active, Paused, Closed, or Archived.
Converse_Desk_Recently_Used_Filters__c	Filter_ID__c	Filter ID	This field contains the ID of list view or Converse App selected on Converse Desk.
Converse_Desk_Recently_Used_Filters__c	Filter_Object__c	Filter Object	This field contains the name of the object on which the List View or Converse App was selected in Converse Desk.
Converse_Desk_Recently_Used_Filters__c	User__c	User	This field contains the user ID that selected List View or Converse App filter in Converse Desk.
Unrelated_Object_Config__c	Parent_Object_Id__c	Parent Object Id	This field contains ID of the Parent Message Object Config record.
SMS_Magic_Security_Setting__c	Api_Key__c	Api Key	This field contains the API key for authentication process.

SMS_Magic_Security_Setting__c	Application_key__c	Application key	This field contains the application key of organization. This is a private key used for application registration.
SMS_Magic_Security_Setting__c	isRegistered__c	isRegistered	This field contains value of the registration status of the application. The value can be TRUE or FALSE.
Object_Metadata_Config__c	Metadata_Id__c	Metadata Id	This field contains ID information of the page created through Interact package.
Object_Metadata_Config__c	Metadata_Label__c	Metadata Label	This field contains the label of the page or button created through Interact package.
Object_Metadata_Config__c	Metadata_Type__c	Metadata Type	This field contains the type of the component created through Interact package. Component is either Page or Button.
Object_Metadata_Config__c	Parent_Object_Id__c	Parent Object Id	This field contains ID information of the parent MOC record for which page or button is created.
global_settings__c	Can_Setup_App__c	Can Setup App	Select this field to enable the user to setup Converge Apps.
global_settings__c	Compliance_Type__c	Compliance Type	This field contains the value of the compliance mechanism used in organization. The values can be: OptIn or OptOut or blank meaning no compliance check required
global_settings__c	Default_Email_Notification_Template__c	Default Email Notification Template	This field contains the ID of the email template used by default for email notification on incoming message.

global_settings__c	Enable_Incoming_Notification__c	Enable Incoming Notification	This field contains the value for new message notification. The value can be: Select for notification or Clear for no notification.
global_settings__c	Is_Coverage_Setup_Complete__c	Is Coverage Setup Complete	This field contains the value about completion on Coverage step in Setup. The value can be Select for successful completion of the Coverage step or Clear for Coverage step not complete.
global_settings__c	Lookup_not_in_outgoing_message__c	Lookup not in outgoing message	Checking this settings would try to lookup to every object present in object config irrespective of whether the latest message from the same number had a lookup to that object or not.
global_settings__c	Max_SMS_Text_Length__c	Max SMS Text Length	This field contains the value of the maximum permissible length for SMS.
global_settings__c	Task_Subject__c	Task Subject	This field contains the value of the Task Subject. Use this value to send automated SMS on task creation.
global_settings__c	Use_Common_Object__c	Use Single Message Object	Select this field to use common object for incoming and outgoing messages.
global_settings__c	Use_Config_for_Incoming_Message_Lookup__c	Use Config for Incoming Message Lookup	Select this field to use incoming lookup logic based on phone number and Sender ID on a setup where incoming messages are stored in separate object.
global_settings__c	Use_Default_SenderId__c	Use Default SenderId	This field contains the value to ensure that only default sender is shown on sender ID selection while sending SMS.

global_settings__c	isDataMigrationAccessible__c	Is Data Migration Accessible	This field contains the value to enable User interface for Data Migration.
global_settings__c	lastExecutedMigrationBatchId__c	Last Executed Migration BatchId	This field contains the ID of last data migration batch. Use this field to identify progress of data migration steps.
Incoming_SMS__c	Campaign__c	Campaign	This field contains the value of the related campaign for incoming.
Incoming_SMS__c	Case__c	Case	This field contains the value of the related case for incoming.
Incoming_SMS__c	Contact__c	Contact	This field contains the value of the related contact for incoming.
Incoming_SMS__c	Conversation__c	Conversation	This field contains the value of the related conversation for incoming.
Incoming_SMS__c	Converse_App_Action__c	Converse App Action	This field contains the value of the related converse app for incoming.
Incoming_SMS__c	Converse_App_Task__c	Converse App Task	This field contains the value of the related app task for incoming.
Incoming_SMS__c	Converse_App__c	Converse App	This field contains the value of the related app for incoming.
Incoming_SMS__c	Favourite__c	Favourite	This field contains the value of the message as favorite if the user selects this field.
Incoming_SMS__c	Inbound_Number__c	Inbound Number	This field contains the value of the To number that can receive incoming SMS.
Incoming_SMS__c	Lead__c	Lead	This field contains the value of the related lead for incoming.
Incoming_SMS__c	MMS_Type__c	Message Type	This field contains the value of the message type. The value can be: SMS or MMS.

Incoming_SMS__c	Mobile_Number__c	Mobile Number	This fields contains the mobile number sending message.
Incoming_SMS__c	Mobile_Number_without_ISD_Code__c	Mobile Number without ISD Code	This fields contains the mobile number sending message without ISD code.
Incoming_SMS__c	New__c	New	Select this field to mark the message as New.
Incoming_SMS__c	ObjectType__c	Object	This field contains the primary object.
Incoming_SMS__c	SMS_Text__c	SMS Text	This field contains the text sent by the client.
Incoming_SMS__c	User__c	User	This field contains the ID of the related user.
Incoming_SMS__c	actionTaken__c	Action Taken	This field contains the action taken on Incoming. The action can be: Create Task, Create Lead, Create Contact, Create Case, etc.
Incoming_SMS__c	external_field__c	External Field	This field contains the ID for external systems.
Incoming_SMS__c	outgoing_sms__c	Outgoing SMS	This field contains the ID of the previous outgoing SMS.
Incoming_SMS__c	taskId__c	taskId	This field contains the related task ID.
Keyword_Action_Config__c	Field_To_Update__c	Field To Update	To be used in future. This field contains the API name of the field to update.
Keyword_Action_Config__c	Keyword__c	Keyword	To be used in future. This field contains the value of the keyword.
Keyword_Action_Config__c	Related_To__c	Related To	To be used in future. This field contains the ID of the related Message Object Config (MOC).
Keyword_Action_Config__c	Value__c	Value	To be used in future. This field contains value to be used in Field To Update.
License__c	Status__c	Status	This field contains the license status. The status can be: Active or Inactive.

License__c	User__c	User	This field contains the user ID to which license is assigned.
Update_Related_Lists__c	Update_Account_Related_List__c	Update Account Related List	Select this field to port incoming and outgoing messages to Account on Lead conversion.
Update_Related_Lists__c	Update_Contact_Related_List__c	Update Contact Related List	Select this field to port incoming and outgoing messages to Contact on Lead conversion.
Update_Related_Lists__c	Update_Opportunity_Related_List__c	Update Opportunity Related List	Select this field to port incoming and outgoing messages to Opportunity on Lead conversion.
Child_Object_Config__c	Parent_Object_Id__c	Parent Object Id	To be used in future. This field contains the ID of the related MOC.
Object_Field_Config__c	Field_Name__c	Field Name	This field contains the field name used by MOC object.
Object_Field_Config__c	Field_Purpose__c	Field Purpose	This field contains the purpose of which field name used by the MOC object.
Object_Field_Config__c	Field_Type__c	Field Type	This field gives information about how to use Field Name.
Object_Field_Config__c	Object_Message_Config__c	Related To Master Object	This field contains the ID of the parent MOC record.
Object_Field_Config__c	Unrelated_Object_Config__c	Unrelated Object Record	This field contains the ID of the Unrelated Object Config. Used only when the purpose is unrelated.
SMS_Template__c	Description__c	Description	This field contains the description of the template.
SMS_Template__c	Name__c	Name	This field contains the name of template.
SMS_Template__c	ObjectName__c	ObjectName	This field contains the Objects for which templates to be created.
SMS_Template__c	Text__c	Text	This field contains the text in the template.

Disable_Triggers_Execution__c	Disable_Incoming_Lookup__c	Disable Incoming Lookup	Select this field to stop lookup and actions happening on incoming messages from managed package code.
Disable_Triggers_Execution__c	Disable_Lead_Conversion__c	Disable Lead Conversion	Select this field to stop migration of messages and conversations on Lead migration.
Disable_Triggers_Execution__c	Disable_Mail_Sending__c	Disable Mail Sending	Select this field to disable managed package code to send email notifications on incoming messages.
Disable_Triggers_Execution__c	Disable_Salesforce_Task__c	Disable Salesforce Task	Select this field to disable sending an automated messages on Salesforce Task creation.
Contact	SMSOptOut__c	SMS Opt Out	This field contains the value to mark the contact as OptOut.
Keyword_Action_Map__c	Action_Type__c	Action Type	This field contains the type of Action. The type can be: Trigger or Response.
Keyword_Action_Map__c	Converse_App_Action__c	Converse App Action	This field contains the lookup of related action.
Keyword_Action_Map__c	Keyword__c	Keyword	This field contains the lookup of related keyword.
Converse_App_User_Map__c	Converse_App__c	Converse App	This field contains the ID of the related Converse App.
Converse_App_User_Map__c	User__c	User	This field contains the ID of the related user.
Action__c	Action_To_Perform__c	Action To Perform	This field contains the Action type to perform The type can be: Create Lead or Case or Task.
Action__c	Action_Type__c	Action Type	This field contains the Action type. The type can be: Automated or Manual.
Action__c	Description__c	Description	This field contains the description of the Action.

MMS_Detail__c	MMS_Type__c	MMS Type	This field contains the type of the MMS. The type can be: Internal or External.
MMS_Detail__c	MMS_Url__c	MMS Url	This field contains the URL of the MMS.
MMS_Detail__c	SMS_History__c	SMS History	This field contains the ID of the related outgoing SMS.
Duration_To_View_History__c	noOfDaysForCutOffDate__c	noOfDaysForCutOffDate	This field contains the value of the number of days for search on outgoing recipient can be done to map to an incoming sender.
Incoming_MMS_Detail__c	Incoming_SMS__c	Incoming SMS	This field contains the ID of the related incoming SMS.
Incoming_MMS_Detail__c	MMS_Type__c	MMS Type	This field contains the type of the MMS. The type can be: Internal or External.
Incoming_MMS_Detail__c	MMS_URL__c	MMS URL	This field contains the URL of the MMS.
Message_Object_Config__c	Name_Field__c	Name Field	This field contains the API name of the name field of the object.
Message_Object_Config__c	Object_Name__c	Object Name	This field contains the object name.
Message_Object_Config__c	Opt_Out_Field_Value__c	Opt Out Field Value	This field contains the value of the OptOut.
Message_Object_Config__c	Opt_Out_Field__c	Opt Out Field	This field contains the API name of OptOut field.
Message_Object_Config__c	Opt_Out_Operator__c	Opt Out Operator	This field contains the operator value to check if the record is opted out.
Action_Parameter__c	Action__c	Action	This field contains the ID of the related Action record.
Action_Parameter__c	Object__c	Object	This field contains the API name of the related MOC.
Action_Parameter__c	Parameter_Name__c	Parameter Name	This field contains the name of the parameter.

Action_Parameter__c	Parameter_Type__c	Parameter Type	This field contains the type of the parameter. The type can be: URL, Field, etc.
Action_Parameter__c	Parameter__c	Parameter Value	This field contains the value of the parameter.
Converse_App_Action__c	Automation_Key__c	Automation Key	This field contains the automation key used in the Process builder/workflows.
Converse_App_Action__c	Converse_App__c	Converse App	This field contains the lookup to the Converse App object.
Converse_App_Action__c	End_Date__c	End Date	This field contains the end date of an Action.
Converse_App_Action__c	Fallback_SenderId__c	Fallback SenderId	This field contains the Fallback sender ID if a sender ID corresponding to criteria is not found. Not specifying this field would fail messages for records where sender selection criteria did not return a valid sender ID.
Converse_App_Action__c	List_View_ID__c	List View ID	This field contains the ID of the list view.
Converse_App_Action__c	Message_App_Trigger_Name__c	Message App Trigger Name	This field contains the name of the message app trigger.
Converse_App_Action__c	Message_App_Trigger__c	Message App Trigger	This field contains the type of the trigger. The type can be: Process Builder, Workflow, Manual, Detail, Pardot. etc.
Converse_App_Action__c	Message_Sequence__c	Message Sequence	This field contains the message sequence.
Converse_App_Action__c	Message_Text__c	Message Text	This field contains the message text used for sending SMS.
Converse_App_Action__c	Mobile_Phone_Field__c	Mobile Phone Field	This field contains the mobile phone field used for sending SMS.
Converse_App_Action__c	Purpose__c	Purpose	This field contains the purpose of the Action.

Converse_App_Action__c	Respect_Subscription_Setting__c	Respect Subscription Setting	This field contains the value on which people get messages. The value can be: Opted Out people do not get messages and Opted In people get messages.
Converse_App_Action__c	SMS_Schedule__c	SMS Schedule	This field contains the ID of the related schedule.
Converse_App_Action__c	SMS_Template__c	SMS Template	This field contains the ID of the related template.
Converse_App_Action__c	SenderIDSelectionCriteria__c	SenderID Selection Criteria	This field contains the value of the sender ID selection criteria. The value can be: Record Owner, Current User, etc.
Converse_App_Action__c	SenderIDSelectionType__c	SenderID Selection Type	This field contains the value of the sender ID selection type. The value can be: Auto or Fixed.
Converse_App_Action__c	Start_Date__c	Start Date	This field contains the start date of the Action.
Converse_App_Action__c	Status__c	Status	This field contains the status of the Action. The status can be: Draft, Active, Paused, etc.
Converse_App_Action__c	Task_Owner_Criteria__c	Task Owner Criteria	This field contains the criteria of the task owner. The criteria can be: Record Owner, Current User.
Converse_App_Action__c	Template_Selection_Criteria__c	Template Selection Criteria	This field contains the criteria of the template selection.
Converse_App_Action__c	Template_Selection_Type__c	Template Selection Type	This field contains the type of the template selection. The type can be: Auto or Fixed.
Converse_App_Action__c	Type__c	Type	This field contains the type of Action. The type can be: Automation, Auto Reply, Schedule, etc.

Converse_Desk_User_Config__c	Listing_Field__c	Listing Field	This field contains the API name of the field that is displayed on the Conversation listing.
Converse_Desk_User_Config__c	Message_Object_Config__c	Message Object Config	This field contains the ID of the MOC for which the config is done.
Converse_Desk_User_Config__c	Template_Field__c	Template Field	This field contains the template field to show. If blank, no template field is shown.
Converse_Desk_User_Config__c	User__c	User	This field contains the ID of the user for whom the config is done.
Converse_App_Task__c	Automation_Key_Reference__c	Automation Key Reference	This field contains the automation key reference.
Converse_App_Task__c	Contact__c	Contact	This field contains the ID of the related contact.
Converse_App_Task__c	Converse_App_Action__c	Converse App Action	This field contains the ID of the related action.
Converse_App_Task__c	ErrorMessages__c	Error Messages	This field contains the error messages.
Converse_App_Task__c	Event_Id__c	Event Id	This field contains the ID of the related event.
Converse_App_Task__c	Incoming_SMS__c	Incoming SMS	This field contains the ID of the related incoming SMS.
Converse_App_Task__c	Lead__c	Lead	This field contains the ID of the related lead.
Converse_App_Task__c	SMS_History__c	SMS History	This field contains the ID of the related SMS history.
Converse_App_Task__c	Status__c	Status	This field contains the value of the transaction status. The value can be: Success or Fail.
Converse_App_Task__c	Task_Id__c	Task Id	This field contains the ID of the related task.
Converse_App_Task__c	Template__c	Template	This field contains the ID of the related template.

Converse_App_Task__c	Type__c	Type	This field contains the value of the transaction type. The value can be: Bulk or Automation.
Converse_App_Template_Map__c	Converse_App__c	Converse App	This field contains the ID of the related app.
Converse_App_Template_Map__c	SMS_Template__c	SMS Template	This field contains the ID of the related SMS template.
Converse_App_Template_Map__c	Type__c	Type	This field contains the value to map the template with Converse Apps
Action_Object__c	Action__c	Action	This field contains the related action.
Action_Object__c	Object__c	Object	This field contains the related message object.
Lead	SMSOptOut__c	SMS Opt Out	Select this field to mark the Lead as OptOut.
Alpha_SenderID_Map__c	Incoming_Sender_ID__c	Incoming Sender ID	This field contains the related Incoming Sender ID.
Alpha_SenderID_Map__c	Outgoing_Sender_ID__c	Outgoing Sender ID	This field contains the related Outgoing Sender ID.
smsMagic__c	Account__c	Account	This field contains the ID of the related Account.
smsMagic__c	Campaign__c	Campaign	This field contains the ID of the related Campaign.
smsMagic__c	Case__c	Case	This field contains the ID of the related Case.
smsMagic__c	Contact__c	Contact	This field contains the ID of the related Contact.
smsMagic__c	Conversation__c	Conversation	This field contains the ID of the related Conversation.
smsMagic__c	Converse_App_Action__c	Converse App Action	This field contains the ID of the related Converse App Action.
smsMagic__c	Converse_App_Task__c	Converse App Task	This field contains the ID of the related Converse App Task.
smsMagic__c	Converse_App__c	Converse App	This field contains the ID of the related Converse App.

smsMagic__c	Country__c	Country	This field contains the value of the recipient country.
smsMagic__c	CreatedOn__c	CreatedOn	This field contains the created date.
smsMagic__c	Direction__c	Direction	This field contains the direction of the message. The direction can be: OUT is for outgoing and IN is for inbound.
smsMagic__c	Is_Text_Unicode__c	Text Unicode	Select this field to make the message Unicode.
smsMagic__c	Lead__c	Lead	This field contains the ID of the related Lead.
smsMagic__c	MMS_Subject__c	MMS Subject	This field contains the subject of the MMS.
smsMagic__c	Message_Type__c	Message Type	This field contains the message type. The type can be: SMS or MMS.
smsMagic__c	Name__c	Name	This field contains the value of the Name of the SMS recipient.
smsMagic__c	New__c	New	Select this field to make the message New.
smsMagic__c	ObjectType__c	ObjectType	This field contains the Object type of the receiver. The type can be: Contact or Lead or User.
smsMagic__c	Opportunity__c	Opportunity	This field contains the ID of the related Opportunity.
smsMagic__c	PhoneNumber__c	Mobile Number	This field contains the mobile number of the recipient.
smsMagic__c	Previous_Message__c	Previous Message	This field contains the lookup of previous message.
smsMagic__c	SMSText__c	SMSText	This field contains the text sent to recipient.
smsMagic__c	SMS_Credits__c	Message Credits	This field contains the credits consumed while sending message.
smsMagic__c	SMS_Template__c	SMS Template	This field contains the ID of the related SMS template.

smsMagic__c	SenderId__c	SenderId	This field contains the ID of the sender.
smsMagic__c	Sent_By__c	Sent By	This field contains the Sent By date.
smsMagic__c	Sent_On__c	Sent On	This field contains the Sent On date.
smsMagic__c	Source__c	Source	This field contains the message source.
smsMagic__c	Status__c	Status	This field contains the status of message. The status can be: Sent, Submitted, Queued, etc.
smsMagic__c	Type__c	Type	This field contains the type of the transaction. The type can be: Incoming or Outgoing.
smsMagic__c	Unformatted_Phone_Number__c	Unformatted Phone Number	This field contains the mobile number in an unformatted way.
smsMagic__c	Use_Default_Sender__c	Use Default Sender	This field contains value of the default sender. The value can be: Record Owner or Current User.
smsMagic__c	User__c	User	for Tasks created for User.
smsMagic__c	disableSMSOnTrigger__c	Disable SMS On Trigger	This field contains the value for SMS History. The value can be: 1 for creating SMS History record only or 0 for making callout and creating SMS History record.
smsMagic__c	external_field__c	External Field	This field contains the ID for external systems.
smsMagic__c	statusMessage__c	Status Message	This field contains the status message.
SMS_Magic_URL_Setting__c	Remote_MMS_Url__c	Remote MMS Url	This field contains the Remote URL for MMS callouts.
SMS_Magic_URL_Setting__c	Remote_Registration_Url__c	Remote Registration Url	This field contains the Remote URL for registration.
SMS_Magic_URL_Setting__c	Remote_URL__c	Remote URL	This field contains the Remote URL for sending SMS.

SMS_Magic_URL_Setting__c	Server_Location__c	Server Location	This field contains the value for server location of the SMS Magic database.
SMS_Schedule__c	Campaign_Statuses__c	Campaign Statuses	This field contains the campaign member statuses.
SMS_Schedule__c	Condition__c	Condition	To be deprecated.
SMS_Schedule__c	Date__c	Date	This field contains the date in GMT format.
SMS_Schedule__c	End_Date__c	End Date	This field contains the end date of schedule.
SMS_Schedule__c	Exclude_Phone_Json__c	Exclude Phone Json	To be deprecated.
SMS_Schedule__c	Failure_Reason__c	Comments	This field contains the failure reason.
SMS_Schedule__c	Job_ID__c	Job ID	This field contains the ID of the schedule job.
SMS_Schedule__c	List_View_Configuration__c	List View Configuration	To be deprecated.
SMS_Schedule__c	Name_Field__c	Name Field	This field contains the Name field.
SMS_Schedule__c	Object__c	Object	This field contains the name of the message object.
SMS_Schedule__c	Optout_Field__c	Optout Field	This field contains the Opt Out field.
SMS_Schedule__c	Phone_Field__c	Phone Field	This field contains the Phone field.
SMS_Schedule__c	Record_Ids__c	Record Ids	This field contains the ID of the record.
SMS_Schedule__c	SMS_Template__c	SMS Template	This field contains ID of the template.
SMS_Schedule__c	SMS_Text__c	SMS Text	This field contains the SMS text.
SMS_Schedule__c	Schedule_JobId__c	Schedule JobId	This field contains the value of the random generatedj ob name.
SMS_Schedule__c	Schedule_Name__c	Schedule Name	This field contains the scheduled job name.
SMS_Schedule__c	Scheduled_Date__c	Scheduled Date	This field contains the scheduled date.
SMS_Schedule__c	Selected_Days_RecurWeek__c	Selected Days RecurWeek	This field contains the days for weekly recurring.

SMS_Schedule__c	Selected_Months_RecurMonthly__c	Selected Months RecurMonthly	This field contains the days for monthly recurring.
SMS_Schedule__c	Selected_Months_RecurYearly__c	Selected Months RecurYearly	This field contains the days for yearly recurring.
SMS_Schedule__c	Selected_User__c	Selected User	This field contains the selected user.
SMS_Schedule__c	SenderId__c	Sender Id	This field contains the ID of the sender.
SMS_Schedule__c	Show_Other_Users__c	Show Other Users	To be deprecated.
SMS_Schedule__c	Status__c	Status	This field contains the status. The status can be: scheduled, queued, etc.
SMS_Schedule__c	Template_Id_Json__c	Template Id Json	To be deprecated.
SMS_Schedule__c	Unrelated_Object_ID__c	Unrelated Object ID	This field contains the ID of the unrelated object.
SMS_Schedule__c	Variable_Day_RecurDay__c	Variable Day RecurDay	To be deprecated.
SMS_Schedule__c	isOptout__c	Send To Optout	Select this field to send SMS to OptOut records.
SMS_Schedule__c	isRecurring__c	isRecurring	This field contains the value stating if the schedule is recurring.
SMS_Schedule__c	recursTypeForDaily__c	recursTypeForDaily	This field contains the value stating if it is daily recurring schedule.
SMS_Schedule__c	recursTypeMonthly__c	recursTypeMonthly	This field contains the value stating if it is monthly recurring schedule.
SMS_Schedule__c	recursTypeYearly__c	recursTypeYearly	This field contains the value stating if it is yearly recurring schedule.
SMS_Schedule__c	recursType__c	recursType	This field contains the type of schedule. The type can be: daily, monthly, or yearly.
SMS_Schedule__c	selectedDateForYear__c	selectedDateForYear	This field contains the selected date for year.
SMS_Schedule__c	selectedDayForMonth1__c	selectedDayForMonth1	This field contains the selected day for start month.
SMS_Schedule__c	selectedDayForMonth2__c	selectedDayForMonth2	This field contains the selected day for end month.

SMS_Schedule__c	selectedMonthForYear__c	selectedMonthForYear	This field contains the selected month for year.
SMS_Schedule__c	selectedMonth__c	selectedMonth	This field contains the selected month.
SMS_Schedule__c	selectedWeekDayForYear__c	selectedWeekDayForYear	This field contains the selected weekday for year.
SMS_Schedule__c	selectedWeekForMonth__c	selectedWeekForMonth	This field contains the selected week for month.
SMS_Schedule__c	selectedWeekForYear__c	selectedWeekForYear	This field contains the selected week for year.
SMS_Schedule__c	variableMonth1__c	variableMonth1	To be deprecated.
SMS_Schedule__c	variableMonth2__c	variableMonth2	To be deprecated.
Conversation_Related_Objects__c	Absolute_Field__c	Absolute Field	This field contains the absolute API path from Conversation to Related object.
Conversation_Related_Objects__c	Conversation_Field__c	Conversation Field	This field contains the reference field of related object on Conversation.
Conversation_Related_Objects__c	MOC__c	MOC	This field contains the ID of the related MOC.
Conversation_Related_Objects__c	Relative_Field__c	Relative Field	This field contains the relative API path from Conversation to Related object.
Conversation_Sender_Map__c	Conversation__c	Conversation	This field contains the ID of the related conversation.
Conversation_Sender_Map__c	SMS_SenderId__c	SMS SenderId	This field contains the ID of the related sender.
License_Management__c	Standard__c	Standard	This field contains the total number of purchased licenses.
SMS_SenderId__c	Description__c	Description	This field contains the description of the sender ID.
SMS_SenderId__c	Email_Notification_Template__c	Email Notification Template	This field contains the ID of the email template used for notification.
SMS_SenderId__c	Label__c	Label	This field contains the label of the sender ID.

SMS_SenderId__c	Notification_Recipient__c	Notification Recipient	This field contains value of the Notification Recipient. The value can be None, Last Sender, etc.
SMS_SenderId__c	Used_For__c	Used For	This field contains the description of the purpose of the sender ID.
SMS_SenderId__c	senderId__c	SenderId	This field contains the ID of the sender.
Conversation__c	Campaign__c	Campaign	This field contains the ID of the related Campaign.
Conversation__c	Contact__c	Contact	This field contains the ID of the related Contact.
Conversation__c	Converse_App_Action__c	Converse App Action	This field contains the ID of the related Converse App Action.
Conversation__c	Converse_App__c	Converse App	This field contains the ID of the related Converse App.
Conversation__c	Last_Incoming_Time__c	Last Incoming Time	This field contains the time of the Last Incoming Message in the Conversation.
Conversation__c	Last_Message_Direction__c	Last Message Direction	This field contains the direction of the Last Message in the Conversation.
Conversation__c	Last_Message_Time__c	Last Message Time	This field contains the time of the Last Message in the Conversation.
Conversation__c	Last_Outgoing_Time__c	Last Outgoing Time	This field contains the time of the Last Outgoing Message in the Conversation.
Conversation__c	Lead__c	Lead	This field contains the ID of the related Lead.
Conversation__c	Mode__c	Mode	This field contains the value of the Mode. The value can be: Auto or Manual.
Conversation__c	New_Count__c	New Count	This field contains the value of the count of new incoming messages.

Conversation__c	Object__c	Object	This field contains the name of the Primary Object of Conversation.
Conversation__c	Purpose__c	Purpose	This field contains the purpose of Conversation.
Conversation__c	State__c	State	This field contains the value of the Conversation status. The value can be: Open or Closed.
Conversation__c	account__c	account	This field contains the ID of the related Account.
Conversation__c	case__c	case	This field contains the ID of the related Case.
Conversation__c	isUnread__c	isUnread	This field identifies if the conversation has unread messages.
Conversation__c	opportunity__c	opportunity	This field contains the ID of the related Opportunity.